

## Aircooled Chillers \ Others

### AirDUCT

Ducted chiller



**Cooling capacity A35/W7:** 40-320 kW

**Compressors:** Scroll

**Refrigerant:** R410a

**Fans:** Centrifugal EC

**Condenser:** CuAl

**Evaporator:** BPHE

**Basic version:** RS485 Modbus, etc.

**Key available options:**

Freecooling \ Inverter or On-Off pump and tank kits \ Coils coating \ Touchscreen display \ EEV \ Low noise \ Heat recovery \ etc.

### CUSTOM Chillers

to customer requested specification



**Cooling capacity A35/CW7:** 5-3000 kW

**Cabinet and piping:** Standard, Stainless steel, etc.

**Compressors:** Screw, Scroll, Reciprocating (inverter available)

**Refrigerants:** HFC (R410A, R134a, R404a, R407C, etc.), HFO (R1234ze, R449A/XP40, etc.), Propane (R290)

**Fans:** Axial, Centrifugal

**Condenser:** Microchannel, CuAl, Coated, Adiabatic cooling, etc.

**Evaporator:** BPHE, Shell&Tube, Remote

**Key applications:**

Aggressive areas \ Industrial \ Refrigeration \ High and low ambient \ Special requirements \ etc.